

TECHNICAL DATA SHEET

THE GOOD OIL WR80 WIRE ROPE LUBRICANT REVOLUTION

The Hammersley Group submit The Good Oil WR80 as a new concept for the future of wire rope lubrication and protection. The Good Oil WR80 represents the culmination of Hammersley's many years in the development of effective, diverse and safe industrial lubricants.



FEATURES AND BENEFITS:

- **Excellent water repellency:** Surrounds and binds strongly to the individual strands of wire, preventing the ingress of any water moisture.
- **Unsurpassed penetration and friction reduction:** Very low friction coefficient indicates effective reduction of friction and more efficient lubrication characteristics.
- **100% active:** The fluid contains no diluents- 100% of the fluid sprayed onto the rope remains as the active penetrant and lubricant.
- **No solvent evaporation:** No change in any characteristic. The concentrate is rapidly absorbed to coat all the rope's fibres, quickly lubricating and relieving friction between strands.
- **Non-hazardous:** The WR80 fluid does not meet the criteria for classification as a hazardous good.
- **Ecologically responsible:** No petroleum ingredients. WR80 is not classified hazardous to the aquatic environment. It is readily biodegradable, and it is not bio-cumulative. The fluid has no Global Warning Potential (GWP) and zero Ozone Depletion Potential (ODP).

APPLICATIONS:

The Good Oil WR80 was developed for the preservation of standing or running wire ropes in all marine environments. It also provides excellent service for the lubrication, protection, and wear resistance of marine chains and mechanisms. Suitable to treat Wire Rope used in a range of lifting, rigging and load securing applications across a wide variety of industries – Maritime, Mining, Construction, Transportation, and Manufacturing.

Examples of use:

- Maritime – mooring & towing • Construction – cranes & elevators
- Mining – drilling & pipeline operations • Transportation – towing & infrastructure (bridges)

DIRECTIONS:

Ready to Use. Can be applied by brush, spray, drip, or bath. Suitable for use in automatic pressure feeders. Apply liberally to ensure inner core of rope is permeated.

Note: New cables or cables regularly maintained will require NO prior preparation. Removal of old grease/soils is preferred, but not essential. Regular applications will enhance protection & working life of the rope.

SAFETY INFORMATION:

The Good Oil WR80 is a very safe product to use however it is always prudent to use good industrial hygiene and practice when using any chemical product:

- Keep out of reach of children
- Harmful if swallowed
- Read Material Safety Data Sheet before use

The Good Oil WR80 is available in:

PRODUCT SIZE	20Lt
PRODUCT CODE	H1025