

TECHNICAL DATA SHEET

Hammersley Australia Pty Ltd

T (02) 4928 2955
F (02) 4928 2405
14 Sandpiper Close, Kooragang
PO Box 150 Hunter Region Mail Centre NSW 2310

www.hammersley.com.au

Silasheen - Silicon Surface Treatment

Prevents Sticking - Creates Slip - Cleans - Lubricates - Protects



FEATURES: BENEFITS:

Highly efficient formula	 Reduces surface friction – ensures quick clean slide. Provides slick, stick free surfaces wherever they are needed. 	
• Protection	 Protects expensive equipment from corrosion and malfunction. Renders many surfaces, water and stain repellent. 	
• Prevention	• Will shed and prevent glues, adhesives, inks and paints from adhering to any solid surface – helps prevent corrosion.	
 Heavy duty 	• Effective in extreme temperatures – 40°C up to 260°C – will not gum or rub off.	
Natural conditioning effect	Rejuvenates rubber, vinyl and plastics.	
• Simple to use	• Saves time and money by reducing clean-up time and costly downtime.	
• Economical	 Adheres strongly to surfaces – for long lasting effect. 	

• Complies with food and drug administration

residual silicone is transferred to food.

requirements provided no more than 10 P.P.M.

APPLICATIONS:

- Rubber, vinyl and plastic surfaces.
- Heavy-duty machinery and equipment.
- Waterproofing.

DIRECTIONS:

1. Make sure surfaces to be treated are clean. Wipe dry before treating.

• Safe to use

- 2. Spray or wipe on Silasheen.
- **3.** Apply thin coats as necessary.
- 4. Remove excess with a clean cloth.

SAFETY INFORMATION:

• Read Material Safety Data Sheet before use.

Silasheen is available in:

PRODUCT SIZE	5L	20L	205L
PRODUCT CODE	301-0005-12	301-0020-12	301-0205-12