

TECHNICAL DATA SHEET

NS36 - Non Chlorinated Cleaning Solvent, Electrical & General

Replaces Chlorinated Hydrocarbon Containing Solvents.



FEATURES:

- Efficient cleaner
- Safer to use
- Complete electrical safety
- Easy to use
- Does not corrode
- Spray bottle safe

BENEFITS:

- High solvent power. Evaporates to complete dryness, leaving no residues.
- High flash point. Non-flammable and non-dangerous goods
- Contains no chlorinated hydrocarbons – very low acute toxicity.
- Does not harm insulation varnish or tarnish plastic rubbers.
- Dielectric strength non conductive at 20 Kv.
- No obnoxious fumes or vapours.
- Has been proven safe after 10 days corrosion tests on aluminium, steel, magnesium, tin, zinc, brass and stainless steel.
- Will not harm viton seals in pump applicators.

APPLICATIONS:

- Electric motors, equipment and components, whether assembled or disassembled.
- Power generators, contact points, end bells and bearings.
- General cleaning and degreasing.
- Instrument parts, bearings and cases.
- Mechanical components.

DIRECTIONS:

1. May be applied by spray, brush or dip methods.
2. In critical areas spray application is often preferred.

SAFETY INFORMATION:

- Read Material Safety Data Sheet before use.
- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Harmful if swallowed.

NS36 is available in:

PRODUCT SIZE	5L	20L	205L	1,000L
PRODUCT CODE	300-0005-59	300-0020-59	300-0205-59	300-1000-59